



PU 75 A sky blue smooth hollow round belt



approx. 80° Shore A

- Recommended pretension:
welded 6 - 8 %
Fitting connector max. 4 - 6 %
- Working tension
approx. 12 daN/cm²

Coefficient of friction μ

- Steel approx. 0,70
- PE approx. 0,40
- HDPE approx. 0,35

FDA/EC/BfR- conform

Order No.	Diameter \varnothing in mm		Cross section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	Ext.	Int.			m	ft	mm	inch	daN	lbs
FBHP75A048HI	4,8	1,8	0,147	1,8	200	656	30	1,2	1,8	3,9
FBHP75A063HI	6,3	2,5	0,261	3,2	100	328	45	1,8	3,1	6,9
FBHP75A080HI	8,0	3,2	0,420	5,1	100	328	55	2,2	5,0	11,1
FBHP75A095HI	9,5	3,8	0,600	7,2	100	328	65	2,6	7,2	15,8
FBHP75A125HI	12,5	5,2	1,020	12,4	50	164	85	3,4	12,2	26,9
FBHP75A150HI	15,0	5,2	1,560	19	50	164	100	4,0	18,7	41,2

* = coefficient of friction $\mu:1$