


Form 1

PU 85 A blue, reinforced glass fiber PU weldable

Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	mm	cm ²	kg/100 m	m	ft	mm	inch	daN	lbs
FBZSP85A170N	17 x 19	1,95	23,63	30	100	240	9,5	50,7	111,5
FBZSP85A220N	22 x 24	3,26	39,1	30	100	280	11,0	84,8	186,5

approx. 88° Shore A

- Recommended pretension 1 - 2% | Working tension: approx. 26 daN/cm²



Form 2

PU 85 A blue, reinforced glass fiber PU weldable

Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	mm	cm ²	kg/100 m	m	ft	mm	inch	daN	lbs
FBBK17X19LGA	17 x 19	2,13	25,6	30	100	290	11,4	55,38	121,8
FBBK22X25LGA	22 x 25	3,65	43,8	30	100	330	13,0	94,9	208,8

approx. 88° Shore A

- Recommended pretension 1 - 2% | Working tension: approx. 26 daN/cm²

* = coefficient of friction μ :1



DE19900551C1
US Patent No. 6,468,656