


PU 85 A green



Form 1

Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	mm	cm ²	kg/100 m	m	ft	mm	inch	daN	lbs
F BSP85A170N	17 x 19	1,95	23,6	30	100	160	6,3	35,12	77,3
F BSP85A220N	22 x 24,5	3,26	39,1	30	100	200	7,9	58,7	129,1

* = coefficient of friction μ :1

approx. 88° Shore A

- Recommended pretension 6 - 8 % | Working tension: approx. 18 daN/cm²

PU 85 A green



Form 2

Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	mm	cm ²	kg/100 m	m	ft	mm	inch	daN	lbs
FBAK17X19GG	17 x 19	2,13	25,6	30	100	180	7,1	38,3	73,3
FBAK22X25GG	22 x 25	3,65	43,8	30	100	230	9,1	65,7	144,5

* = coefficient of friction μ :1

approx. 88° Shore A

- Recommended pretension 6 - 8 % | Working tension: approx. 18 daN/cm²

PU 85 A green, reinforced polyester



Form 2

Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	mm	cm ²	kg/100 m	m	ft	mm	inch	daN	lbs
FBBK17X19GGA	17 x 19	2,13	25,6	30	100	180	7,1	72,4	159,3
FBBK22X25GGA	22 x 25	3,65	43,8	30	100	250	9,8	124,1	273,0

* = coefficient of friction μ :1

approx. 88° Shore A