

Form 1 without notch

PU 90 A white

Form 1


Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	mm	cm ²	kg/100 m	m	ft	mm	inch	daN	lbs
FBSP90A1700N	17 x 19	1,95	23,6	30	100	180	7,1	48,8	107,3
FBSP90A2200N	22 x 24,5	3,26	39,1	30	100	230	9,1	81,5	179,3

ca. 92° Shore A

* = coefficient of friction μ :1

- Recommended pretension 4 - 6 % | Working tension: approx. 25 daN/cm²

Form 2 without notch

PU 90 A white

Form 2

Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	mm	cm ²	kg/100 m	m	ft	mm	inch	daN	lbs
FBBL17X19WG	17 x 19	2,13	25,6	30	100	210	8,3	53,3	117,2
FBBL22X25WG	22 x 25	3,65	43,8	30	100	250	9,8	91,3	200,8

approx. 92° Shore A

* = coefficient of friction μ :1

- Recommended pretension 4 - 6 % | Working tension: approx. 25 daN/cm²