

PU 75 A red smooth



Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	mm	cm ²	kg/100 m	m	ft	mm	inch	daN	lbs
FBKP75A06	6 x 4 (Y)	0,19	2,3	100	328	35	1,4	2,5	5,5
FBKP75A08	8 x 5 (M)	0,32	4	100	328	40	1,6	4,2	9,2
FBKP75A10	10 x 6 (Z)	0,48	6	50	164	50	2,0	6,2	13,6
FBKP75A13	13 x 8 (A)	0,82	10	50	164	80	3,2	10,5	23,1
FBKP75A17	17 x 11 (B)	1,46	18	50	164	100	3,9	19,0	41,8
FBKP75A22	22 x 14 (C)	2,40	29	50	164	145	5,7	31,0	68,2
FBKP75A32	32 x 20 (D)	5,00	62	25	82	210	8,3	65,0	143,0

approx. 80° Shore A

- Recommended pretension
6 - 8 %
- Working tension
approx. 13 daN/cm²

* = coefficient of friction μ :1

Coefficient of friction μ : Steel: approx. 0,70 | PE: approx. 0,40 | HDPE: approx. 0,35