



PU 80 A orange/transparent smooth

available as 3-grooved V-Belt
17 x 11 and 22 x 14 mm



approx. 84° Shore A

- Recommended pretension
6 - 8 %
- Working tension
approx. 15 daN/cm²

Profile dimension	Cross section	Weight	Standard Roll orange/transp.		Recommended pulley \emptyset		Working Load/Belt*	
			mm	cm ²	kg/100 m	m	ft	mm
6x4 (Y)	0,19	2,3	30/100	100/328	40	1,6	2,9	6,4
8x5 (M)	0,32	4	30/100	100/328	45	1,8	4,8	10,6
10x6 (Z)	0,48	6	30/50	100/164	55	2,2	7,2	15,8
13x8 (A)	0,82	10	30/50	100/164	85	3,3	12,3	27,1
17x11 (B)	1,46	18	30/50	100/164	110	4,3	21,9	48,2
22x14 (C)	2,40	29	30/50	100/164	150	5,9	36,0	79,2
32x20 (D)	5,00	62	30/25	100/82	220	8,7	75,0	165,0

* = coefficient of friction μ :1

Coefficient of Friction μ : Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/BfR- conform