


# PU 80 A transparent smooth



**approx. 84° Shore A**

- Recommended pretension  
6 - 8 %
- Working tension  
approx. 15 daN/cm<sup>2</sup>

Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley $\varnothing$		approx. Working Load/Belt*	
	mm	cm <sup>2</sup>	kg/100 m	m	ft	mm	inch	daN	lbs
FBKP80A06TR	6 x 4 (Y)	0,19	2,3	100	328	40	1,6	2,9	6,4
FBKP80A08TR	8 x 5 (M)	0,32	4	100	328	45	1,8	4,8	10,6
FBKP80A10TR	10 x 6 (Z)	0,48	6	50	164	55	2,2	7,2	15,8
FBKP80A13TR	13 x 8 (A)	0,82	10	50	164	85	3,3	12,3	27,1
FBKP80A17TR	17 x 11 (B)	1,46	18	50	164	110	4,3	21,9	48,2
FBKP80A22TR	22 x 14 (C)	2,40	29	50	164	150	5,9	36,0	79,2
FBKP80A32TR	32 x 20 (D)	5,00	62	25	82	220	8,7	75,0	165,0

\* = coefficient of friction  $\mu$ :1

**Coefficient of friction  $\mu$ :** Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30 | **FDA/EC/BfR-conform**