


PU 85 A PLUS blue matt finish



Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	mm	cm ²	kg/100 m	m	ft	mm	inch	daN	lbs
FBKP85A06BP	6 x 4 (Y)	0,19	2,3	100	328	45	1,8	4,2	9,2
FBKP85A08BP	8 x 5 (M)	0,32	4	100	328	50	2,0	7,0	15,5
FBKP85A10BP	10 x 6 (Z)	0,48	6	50	164	70	2,8	10,6	23,2
FBKP85A13BP	13 x 8 (A)	0,82	10	50	164	90	3,5	18,0	39,7
FBKP85A17BP	17 x 11 (B)	1,46	18	50	164	120	4,7	32,1	70,7
FBKP85A22BP	22 x 14 (C)	2,40	29	50	164	160	6,3	52,8	116,2
FBKP85A32BP	32 x 20 (D)	5,00	62	25	82	230	9,1	110,0	242,0

approx. 88° Shore A

- Recommended pretension
4-6 %
- Working tension
approx. 22 daN/cm²

* = coefficient of friction μ :1

Coefficient of friction μ : Steel: approx. 0,60 | PE: approx. 0,30 | HDPE: approx. 0,25



DE19900551C1
US Patent No. 6,468,656