



## PU 85 A green smooth

### approx. 88° Shore A

- Recommended pretension  
6 - 8 %
- Working tension  
approx. 18 daN/cm<sup>2</sup>

Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley Ø		approx. Working Load/Belt*	
	mm	cm <sup>2</sup>	kg/100 m	m	ft	mm	inch	daN	lbs
FBKP85A06	6 x 4 (Y)	0,19	2,3	100	328	45	1,8	3,4	7,5
FBKP85A08	8 x 5 (M)	0,32	4	100	328	50	2,0	5,7	12,5
FBKP85A10	10 x 6 (Z)	0,48	6	50	164	70	2,8	8,6	18,9
FBKP85A13	13 x 8 (A)	0,82	10	50	164	90	3,5	14,7	32,3
FBKP85A17	17 x 11 (B)	1,46	18	50	164	120	4,7	26,0	57,2
FBKP85A22	22 x 14 (C)	2,40	29	50	164	160	6,3	43,0	94,6
FBKP85A32	32 x 20 (D)	5,00	62	25	82	230	9,1	96,0	211,2

\* = coefficient of friction  $\mu$ :1

Coefficient of friction  $\mu$ : Steel: approx. 0,60 | PE: approx. 0,30 | HDPE: approx. 0,25