



PU 90 A white smooth

approx. 92° Shore A

- Recommended pretension
4 - 6 %
- Working tension
approx. 25 daN/cm²

| Order No. | Profile dimension | Cross section | approx. Weight | Standard Roll | | Recommended Min. pulley \varnothing | | approx. Working Load/Belt* | |
|-------------------|-------------------|-----------------|----------------|---------------|-----|---------------------------------------|------|----------------------------|-------|
| | mm | cm ² | kg/100 m | m | ft | mm | inch | daN | lbs |
| FBKP90A08 | 8 x 5 (M) | 0,32 | 4 | 100 | 328 | 60 | 2,4 | 8,0 | 17,6 |
| FBKP90A10 | 10 x 6 (Z) | 0,48 | 6 | 50 | 164 | 80 | 3,2 | 12,0 | 26,4 |
| FBKP90A13 | 13 x 8 (A) | 0,82 | 10 | 50 | 164 | 100 | 3,9 | 20,0 | 44,0 |
| FBKP90A17 | 17 x 11 (B) | 1,46 | 18 | 50 | 164 | 140 | 5,5 | 36,0 | 79,2 |
| FBKP90A22 | 22 x 14 (C) | 2,40 | 29 | 50 | 164 | 200 | 7,9 | 60,0 | 132,0 |
| FBKP90A32 (natur) | 32 x 20 (D) | 5,00 | 62 | 25 | 82 | 320 | 12,6 | 125,0 | 275,0 |

* = coefficient of friction μ :1

Coefficient of friction μ : Steel: approx. 0,50 | PE: approx. 0,30 | HDPE: approx. 0,25



Available with cogged bottom on request**

Red upon request