

**55° Shore D -
approx. 100° Shore A**


- Recommended pretension 2 - 4 %
- Working tension approx. 50 daN/cm²

Polyester TPE 55 D beige/blue smooth

Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley \varnothing		approx. Working Load/Belt*	
	mm	cm ²	kg/100 m	m	ft	mm	inch	daN	lbs
FBKH55D08B (beige)	8 x 5 (M)	0,32	4	100	328	80	3,2	16,0	35,2
FBKH55D10B (beige)	10 x 6 (Z)	0,48	6	50	164	100	3,9	24,0	52,8
FBKH55D13 (blue)	13 x 8 (A)	0,82	10	50	164	120	4,7	40,0	88,0
FBKH55D17 (blue)	17 x 11 (B)	1,46	18	50	164	160	6,3	73,0	160,6
FBKH55D22 (blue)	22 x 14 (C)	2,40	29	50	164	240	9,5	120,0	264,0

* = coefficient of friction μ :1

Coefficient of friction μ : Steel: approx. 0,35 | PE: approx. 0,15 | HDPE: approx. 0,10 | **FDA/EC/BfR-conform**



Available with coggated bottom on request**