



## PU 70 A transparent smooth V-guide profiles

Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley $\varnothing$		approx. Working Load/Belt*	
	mm	cm <sup>2</sup>	kg/100 m	m	ft	mm	inch	daN	lbs
FBKH6YTG	6 x 4 (Y)	0,19	2,3	150	500	30	1,2	1,9	4,2
FBKH8MTG	8 x 5 (M)	0,32	4	150	500	35	1,4	3,2	7,0
FBKH10ZTG	10 x 6 (Z)	0,48	6	150	500	45	1,8	4,8	10,6
FBKH13ATG	13 x 8 (A)	0,82	10	150	500	75	2,9	8,2	18,0
FBKH17BTG	17 x 11 (B)	1,46	18	100	328	105	4,1	14,6	32,1
FBKH22CTG	22 x 14 (C)	2,40	29	50	164	140	5,5	24,0	52,8

**approx. 76° Shore A**

• Recommended pretension 6-8 %

• Working tension approx. 10 daN/cm<sup>2</sup>

\* = coefficient of friction  $\mu$ :1

**Coefficient of friction  $\mu$ :** Steel: approx. 0,70 | PE: approx. 0,40 | HDPE: approx. 0,35 | FDA/EC/BfR-conform