


PU 75 A transparent smooth

Order No.	Profile thickness		max. Profile width		Standard Roll		Recommended min. pulley \varnothing	
	mm	inch	mm	inch	ft	m	mm	inch
FBFI150X1TG	1,0	3/64	150	5,9	100	30	10,0	0,2
FBFI150X16TG	1,6	1/16	150	5,9	100	30	15,0	0,3
FBFI150X2TG	2,0	5/64	150	5,9	100	30	20,0	0,4
FBFI150X3TG	3,0	1/8	150	5,9	100	30	25,0	0,8
FBFI150X4TG	4,0	5/32	150	5,9	100	30	35,0	1,2

approx. 80° Shore A

- Recommended pretension 1 - 2 %
- Working tension approx. 13 daN/cm²

Coefficient of friction μ : Steel: approx. 0,70 | PE: approx. 0,40 | HDPE: approx. 0,35 | FDA/EC/BfR-conform



PU 75 A sky blue smooth

Order No.	Profile thickness		max. Profile width		Standard Roll		Recommended min. pulley \varnothing	
	mm	inch	mm	inch	ft	m	mm	inch
FBFI100X1LG	1,0	3/64	150	5,9	100	30	10,0	0,2
FBFI150X16LG	1,6	1/16	150	5,9	100	30	15,0	0,3
FBFI150X2LG	2,0	5/64	150	5,9	100	30	20,0	0,4
FBFI150X3LG	3,0	1/8	150	5,9	100	30	25,0	0,8
FBFI150X4LG	4,0	5/32	150	5,9	100	30	35,0	1,2

approx. 80° Shore A

- Recommended pretension 1 - 2 %
- Working tension approx. 13 daN/cm²

Coefficient of friction μ : Steel: approx. 0,70 | PE: approx. 0,40 | HDPE: approx. 0,35 | FDA/EC/BfR-conform