


Ready-made belts



PU 80 A orange smooth

approx. 84° Shore A

- Recommended pretension 1 - 2 %
- Working tension
approx. 15 daN/cm²

Order No.	Profile thickness		max. Profile width		Standard Roll		Recommended min. pulley \varnothing	
	mm	inch	mm	inch	ft	m	mm	inch
FBFJOG1	1,6	1/16	12,5	1/2	100	30	15	0,6
FBFJOG2	1,6	1/16	19	3/4	100	30	15	0,6
FBFJOG3	1,6	1/16	38	1 ¹ / ₂	100	30	15	0,6
FBFJOG4	1,6	1/16	44	1 ³ / ₄	100	30	15	0,6
FBFJOG5	1,6	1/16	50	2	100	30	15	0,6
FBFJOG6	1,6	1/16	76	3	100	30	15	0,6
FBFJOG7	2,4	3/32	25	1	100	30	20	0,8
FBFJOG8	2,4	3/32	32	1 ¹ / ₄	100	30	20	0,8
FBFJOG9	2,4	3/32	48	1 ¹ / ₂	100	30	20	0,8
FBFJOG10	2,4	3/32	50	2	100	30	20	0,8
FBFJOG11	3,2	1/8	16	5/8	100	30	25	1,0
FBFJOG12	3,2	1/8	25	1	100	30	25	1,0

Coefficient of friction μ : Steel: approx. 0,60 | PE: approx. 0,30 | HDPE: approx. 0,25 | FDA/EC/BfR-conform