


PU 85 A green smooth



approx. 88° Shore A

- Recommended pretension 1 - 2%
- Working tension
approx. 18 daN/cm²

Order No.	Profile thickness		max. Profile width		Standard Roll		Recommended min. pulley ∅	
	mm	inch	mm	inch	ft	m	mm	inch
FBFK100X1GG	1,0	3/64	150	5,9	100	30	15,0	0,5
FBFK150X16GG	1,6	1/16	150	5,9	100	30	20,0	0,6
FBFK150X2GG	2,0	5/64	150	5,9	100	30	30,0	1,2
FBFK150X3GG	3,0	1/8	150	5,9	100	30	35,0	1,4
FBFK150X4GG	4,0	5/32	150	5,9	100	30	45,0	1,8

Coefficient of friction μ : Steel: approx. 0,60 | PE: approx. 0,30 | HDPE: approx. 0,25

PU 85 A transparent smooth



approx. 88° Shore A

- Recommended pretension 1 - 2%
- Working tension
approx. 18 daN/cm²

Order No.	Profile thickness		max. Profile width		Standard Roll		Recommended min. pulley ∅	
	mm	inch	mm	inch	ft	m	mm	inch
FBFK150X1TG	1,0	3/64	150	5,9	100	30	15,0	0,5
FBFK150X16TG	1,6	1/16	150	5,9	100	30	20,0	0,6
FBFK150X2TG	2,0	5/64	150	5,9	100	30	30,0	1,2
FBFK150X3TG	3,0	1/8	150	5,9	100	30	35,0	1,4
FBFK150X4TG	4,0	5/32	150	5,9	100	30	45,0	1,8

Coefficient of friction μ : Steel: approx. 0,60 | PE: approx. 0,30 | HDPE: approx. 0,25 | FDA/EC/BfR-conform