


Sidewalls



Sidewalls white

Type	Item number	Height (mm) H	Wave width (mm) W	Base width (mm) W1	Pitch of waves (mm) P	Aprox. Weight (g/m)	Min. pulley diameter \varnothing (mm)	Recommended pulley diameter \varnothing (mm)	Standard rail (m)	Hardness (Shore A)
U20W Flex	FBVFH020W	20,00	23,00	32,00	25,40	174	35	70	100	85
U30W Flex	FBVFH030W	30,00	23,00	32,00	25,40	220	55	80	100	85
U40W Flex	FBVFH040W	40,00	23,00	32,00	25,40	265	75	90	100	85
U50W Flex	FBVFH050W	50,00	23,00	32,00	25,40	310	80	100	100	85
U60W Flex	FBVFH060W	60,00	45,00	55,00	50,80	445	90	110	100	85
U80W Flex	FBVFH080W	80,00	45,00	55,00	50,80	544	125	130	100	85
U100W Flex	FBVFH100W	100,00	45,00	55,00	50,80	642	155	160	100	85
U120W Flex	FBVFH120W	120,00	45,00	55,00	50,80	741	170	185	100	85

FDA/EC/BfR-conform

Sidewalls apple green

Type	Item number	Height (mm) H	Wave width (mm) W	Base width (mm) W1	Pitch of waves (mm) P	Aprox. Weight (g/m)	Min. pulley diameter \varnothing (mm)	Recommended pulley diameter \varnothing (mm)	Standard rail (m)	Hardness (Shore A)
U20W Flex	FBVFH020G	20,00	23,00	32,00	25,40	174	35	70	100	85
U30W Flex	FBVFH030G	30,00	23,00	32,00	25,40	220	55	80	100	85
U40W Flex	FBVFH040G	40,00	23,00	32,00	25,40	265	75	90	100	85
U50W Flex	FBVFH050G	50,00	23,00	32,00	25,40	310	80	100	100	85
U60W Flex	FBVFH060G	60,00	45,00	55,00	50,80	445	90	110	100	85
U80W Flex	FBVFH080G	80,00	45,00	55,00	50,80	544	125	130	100	85
U100W Flex	FBVFH100G	100,00	45,00	55,00	50,80	642	155	160	100	85
U120W Flex	FBVFH120G	120,00	45,00	55,00	50,80	741	170	185	100	85

FDA/EC/BfR-conform

Sidewalls sky blue



Type	Item number	Height (mm) H	Wave width (mm) W	Base width (mm) W1	Pitch of waves (mm) P	Aprox. Weight (g/m)	Min. pulley diameter \varnothing (mm)	Recommended pulley diameter \varnothing (mm)	Standard rail (m)	Hardness (Shore A)
U20W Flex	FBVFH020L	20,00	23,00	32,00	25,40	174	35	70	100	85
U30W Flex	FBVFH030L	30,00	23,00	32,00	25,40	220	55	80	100	85
U40W Flex	FBVFH040L	40,00	23,00	32,00	25,40	265	75	90	100	85
U50W Flex	FBVFH050L	50,00	23,00	32,00	25,40	310	80	100	100	85
U60W Flex	FBVFH060L	60,00	45,00	55,00	50,80	445	90	110	100	85
U80W Flex	FBVFH080L	80,00	45,00	55,00	50,80	544	125	130	100	85
U100W Flex	FBVFH100L	100,00	45,00	55,00	50,80	642	155	160	100	85
U120W Flex	FBVFH120L	120,00	45,00	55,00	50,80	741	170	185	100	85

FDA/EC/BfR-conform

Sidewalls blue green

Type	Item number	Height (mm) H	Wave width (mm) W	Base width (mm) W1	Pitch of waves (mm) P	Aprox. Weight (g/m)	Min. pulley diameter \varnothing (mm)	Recommended pulley diameter \varnothing (mm)	Standard rail (m)	Hardness (Shore A)
U20W Flex	FBVFH020LG	20,00	23,00	32,00	25,40	174	35	70	100	85
U30W Flex	FBVFH030LG	30,00	23,00	32,00	25,40	220	55	80	100	85
U40W Flex	FBVFH040LG	40,00	23,00	32,00	25,40	265	75	90	100	85
U50W Flex	FBVFH050LG	50,00	23,00	32,00	25,40	310	80	100	100	85
U60W Flex	FBVFH060LG	60,00	45,00	55,00	50,80	445	90	110	100	85
U80W Flex	FBVFH080LG	80,00	45,00	55,00	50,80	544	125	130	100	85
U100W Flex	FBVFH100LG	100,00	45,00	55,00	50,80	642	155	160	100	85
U120W Flex	FBVFH120LG	120,00	45,00	55,00	50,80	741	170	185	100	85

FDA/EC/BfR-conform



PU cleats white/green/blue

Type	Item number	Color	Height (mm) H	Foot Width (mm) W	Standard length per piece (m)	Standard roll	Weight (g/m)	Hardness (Shore A)
PU Thin Cleat 20 white	FBCJ020WT	white	20,00	8,00	3,0	80 pcs. = 240m	75,00	92
PU Thin Cleat 30 white	FBCJ030WT	white	30,00	9,00	3,0	50 pcs. = 150m	109,00	92
PU Thin Cleat 40 white	FBCJ040WT	white	40,00	9,00	3,0	48 pcs. = 144m	129,00	92
PU Thin Cleat 20 green	FBCJ020GT	green	20,00	8,00	3,0	80 pcs. = 240m	75,00	92
PU Thin Cleat 30 green	FBCJ030GT	green	30,00	9,00	3,0	50 pcs. = 150m	109,00	92
PU Thin Cleat 40 green	FBCJ040GT	green	40,00	9,00	3,0	48 pcs. = 144m	129,00	92
PU Thin Cleat 20 blue	FBCJ020LT	blue	20,00	8,00	3,0	80 pcs. = 240m	75,00	92
PU Thin Cleat 30 blue	FBCJ030LT	blue	30,00	9,00	3,0	50 pcs. = 150m	109,00	92
PU Thin Cleat 40 blue	FBCJ040LT	blue	40,00	9,00	3,0	48 pcs. = 144m	129,00	92

FDA/EC/BfR-conform