



FEATURES AT A GLANCE

The patented Friction welding machine RS02 for polyurethane profiles eliminates downtime with a perfect splice every time!

- User-friendly and easy handling.
- No long heating-up and set-up times, spliced within seconds.
- Precise pressure and automatical 0-positioning prevents uneven welds and premature failure.
- Automatic alignment ensures that the belt ends are aligned perfectly.
- Temperature variation is never a concern (no guess-work).
- Without the risk of injury or fire due to hot metal.
- Due to its small size the RS02 press can be used in confined spaces.
- Thanks to its exchangeable jaws the RS02 is suitable for splicing many different profiles up to Ø 6 mm made of Polyurethane.
- 100% repeatability.

Perfect splice within seconds!

Call us. We would be glad to help you! +49(0) 7684/907-0



The RS02 Friction welding machine is the perfect solution for fast and perfect welding polyurethane profiles.

Exchangeable jaws for

different profiles

With the RS02 prevent belt breaks or expensive downtimes!

Scope of delivery:

- 1 pc. Friction welding machine RS02
- 1 set of standard profile jaws at your choice
- 1 pc. Allen key
- 1 pc. Scissors AS02
- 1 pc. Edge cutter SE02
- 1 pc. Carrying bag with durable and predective foam inlay

Dimensions (HxWxD): 390x105x123 mm Weight: approx. 2452 g