

Hollow Round Belts

PU75A sky blue smooth



approx. 80° Shore A (±3)

Recommended Pretension 4...8%

Coeff. of friction μ steel approx. 0,7

Coeff. of friction μ PE approx. 0,4

Coeff. of friction μ HDPE approx. 0,35

FDA/EC compliant

Article no.	Diameter \varnothing		approx. weight kg/100m	Standard roll		Recommended min. pulley \varnothing		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
	mm	inch		m	ft	mm	inch	Standard N	Standard kg	lbs
FBHP75A048HI	4,8	3/16	1,8	200	656	30	1,2	19	3,7	8,2
FBHP75A063HI	6,3	1/4	3,2	100	328	45	1,8	32	6,3	13,9
FBHP75A080HI	8	5/16	5,1	100	328	55	2,2	51	10,1	22,3
FBHP75A095HI	9,5	3/8	7,2	100	328	65	2,6	71	14,3	31,5
FBHP75A125HI	12,5	1/2	12,4	50	164	85	3,4	122	24,4	53,7
FBHP75A150HI	15	19/32	19	50	164	100	4	187	37,3	82,2

Characteristics



FDA (Food and Drug Administration)

FDA/EC conformity for direct food contact



Vegan

Use of raw materials from non-animal origin



Hydrolysis resistance

Hydrolysis resistance (HY). Suitable for humid environments.



microbial resistant

Microbial resistant materials do not provide a breeding ground for microorganisms.



Cold-flexible

Particularly flexible at low temperatures down to -30°C

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 04/2026