

Hollow Round Belts

**PU85A yellow smooth**



approx. 88° Shore A (±3)

Recommended Pretension 4...8%

Coeff. of friction  $\mu$  steel approx. 0,6

Coeff. of friction  $\mu$  PE approx. 0,35

Coeff. of friction  $\mu$  HDPE approx. 0,3

Article no.	Diameter $\emptyset$		approx. weight kg/100m	Standard roll		Recommended min. pulley $\emptyset$		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
	mm	inch		m	ft	mm	inch	Standard N	Standard kg	lbs
FBHP85A048GE	4,8	3/16	1,8	200	656	35	1,4	31	6,2	13,7
FBHP85A063GE	6,3	1/4	3,2	100	328	55	2,2	53	10,5	23,2
FBHP85A080GE	8	5/16	5,1	100	328	65	2,6	84	16,9	37,2
FBHP85A095GE	9,5	3/8	7,2	100	328	75	3	119	23,8	52,5
FBHP85A125GE	12,5	1/2	12,4	50	164	100	3,9	203	40,6	89,5
FBHP85A150GE	15	19/32	19	50	164	120	4,7	311	62,2	137,1

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 05/2026