

Hollow Round Belts

PU85A green roughened



approx. 88° Shore A (±3)

Recommended Pretension 4...8%

Coeff. of friction μ steel approx. 0,45

Coeff. of friction μ PE approx. 0,3

Coeff. of friction μ HDPE approx. 0,25

Article no.	Diameter \varnothing		approx. weight kg/100m	Standard roll		Recommended min. pulley \varnothing		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
	mm	inch		m	ft	mm	inch	Standard N	Standard kg	Standard lbs
FBHP85A048R	4,8	3/16	1,8	200	656	35	1,4	31	6,2	13,7
FBHP85A063R	6,3	1/4	3,2	100	328	55	2,2	53	10,5	23,2
FBHP85A080R	8	5/16	5,1	100	328	65	2,6	84	16,9	37,2
FBHP85A095R	9,5	3/8	7,2	100	328	75	3	119	23,8	52,5
FBHP85A125R	12,5	1/2	12,4	50	164	100	3,9	203	40,6	89,5
FBHP85A150R	15	19/32	19	50	164	120	4,7	311	62,2	137,1

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 04/2026