





Quality: PU90A

Article No.: FBHP90A125

Color: white

GENERAL PROFILE INFORMATION			
Profile Category	Hollow Round Belts	k1% relaxed (standard)	46,7 N 266,3 lbf
Profile design	Without reinforcement	k1% static (standard)	58,4 N 332,9 lbf
Type of reinforcement	n/a	Weight	12,4 kg/100m
Processing Type	n/a	Temperature Range	-20°+60°C
Recommended Min. pulley Ø	100 mm	Standard Roll	50 m
Recommended Pretension	35%	Chemical Resistance	upon request

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	92° Shore A (±3)	n/a
Color	white	n/a
Diameter Ø	12,5 mm (1/2 inch)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,5 PE: 0,3 HDPE: 0,25	n/a
Features	n/a	n/a
n/a	n/a	n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 12/2025