

Hollow Round Belts

PU90A white smooth



approx. 92° Shore A (±3)

Recommended Pretension 3...5%

Coeff. of friction μ steel approx. 0,5

Coeff. of friction μ PE approx. 0,3

Coeff. of friction μ HDPE approx. 0,25

Article no.	Diameter $\emptyset$		approx. weight kg/100m	Standard roll		Recommended min. pulley $\emptyset$		DRIVE Fmax/belt Standard N	TRANSPORT max. conveying weight Standard	
	mm	inch		m	ft	mm	inch		kg	lbs
FBHP90A048	4,8	3/16	1,8	200	656	35	1,4	36	7,2	15,8
FBHP90A063	6,3	1/4	3,2	100	328	55	2,2	60	12,1	26,6
FBHP90A080	8	5/16	5,1	100	328	65	2,6	97	19,4	42,8
FBHP90A095	9,5	3/8	7,2	100	328	75	3	137	27,4	60,4
FBHP90A125	12,5	1/2	12,4	50	164	100	3,9	233	46,7	102,9
FBHP90A150	15	19/32	19	50	164	120	4,7	358	71,5	157,6

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 08/2026