

Round belts

## PU65A ultramarine blue smooth



Article no.	Diameter Ø		approx. weight	Standard roll		Recommended min. pulley ØØ		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
	mm	inch		m	ft	mm	inch		Standard N	Standard lbs
FBRP65A040UB	4	5/32	1,5	200	656	22	0,9	10,0	2,0	4,5
FBRP65A050UB	5	1/5	2,4	100	328	32	1,3	15,7	3,1	7,0
FBRP65A060UB	6	7/32	3,4	100	328	40	1,6	22,6	4,5	10,1

approx. 72° Shore A (±3)

Recommended Pretension 4...8%

Coeff. of friction µ steel approx. 0,85

Coeff. of friction µ PE approx. 0,65

Coeff. of friction µ HDPE approx. 0,55

FDA/EC compliant

### Characteristics


**FDA (Food and Drug Administration)**  
 FDA/EC conformity for direct food contact

**Vegan**  
 Use of raw materials from non-animal origin

**Hydrolysis resistance**  
 Hydrolysis resistance (HY). Suitable for humid environments.

**microbial resistant**  
 Microbial resistant materials do not provide a breeding ground for microorganisms.

**Cold-flexible**  
 Particularly flexible at low temperatures down to -30°C

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 02/2026