

Round belts
PU65A ultramarine blue smooth



Article no.	Diameter \varnothing		approx. weight kg/100m	Standard roll		Recommended min. pulley \varnothing		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
	mm	inch		m	ft	mm	inch	Standard N	Standard kg	Standard lbs
FBRP65A040UB	4	5/32	1,5	200	656	22	0,9	10,0	2,0	4,5
FBRP65A050UB	5	1/5	2,4	100	328	32	1,3	15,7	3,1	7,0
FBRP65A060UB	6	7/32	3,4	100	328	40	1,6	22,6	4,5	10,1

approx. 72° Shore A (± 3)

Recommended Pretension 4...8%

Coeff. of friction μ steel approx. 0,85

Coeff. of friction μ PE approx. 0.65

Coeff. of friction μ HDPE approx. 0.55

FDA/EC compliant

Characteristics



FDA (Food and Drug Administration)

FDA/EC conformity for direct food contact



Vegan
 Use of raw materials from non-animal origin



Hydrolysis resistance
 Hydrolysis resistance (HY). Suitable for humid environments.



microbial resistant
 Microbial resistant materials do not provide a breeding ground for microorganisms.



Cold-flexible
 Particularly flexible at low temperatures down to -30°C

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 06/2026