

Round belts
PU75A plus orange matt



approx. 80° Shore A (±3)

Recommended Pretension 3...6%

Coeff. of friction μ steel approx. 0,7

Coeff. of friction μ PE approx. 0,4

Coeff. of friction μ HDPE approx. 0,35

Article no.	Diameter \varnothing		approx. weight kg/100m	Standard roll		Recommended min. pulley \varnothing		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
	mm	inch		m	ft	mm	inch	Standard N	Standard kg	Standard lbs
FBRI020OG	2	5/64	0,5	200	656	10	0,4	4	0,8	1,7
FBRI030OG	3	1/8	0,9	200	656	20	0,8	9	1,8	3,9
FBRI040OG	4	5/32	1,6	200	656	30	1,2	16	3,2	7,0
FBRI048OG	4,8	3/16	2,2	200	656	35	1,4	23	4,6	10,1
FBRI050OG	5	1/5	2,4	100	328	40	1,6	25	4,9	10,9
FBRI060OG	6	7/32	3,4	100	328	50	2	36	7,1	15,7
FBRI063OG	6,3	1/4	3,8	100	328	55	2,2	39	7,9	17,3
FBRI080OG	8	5/16	6	100	328	65	2,6	89	17,9	39,4
FBRI095OG	9,5	3/8	8,5	100	328	75	3	99	19,8	43,6
FBRI100OG	10	7/16	9,4	50	164	80	3,2			

Characteristics



Low elongation
 Patented "PLUS" material mix for reduced elongation.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 06/2026