





Quality: PU80A SAFE
Article No.: FBRJ143LGM
Color: capri blue









GENERAL PROFILE INFORMATION				
Profile Category	Round belts	k1% relaxed (standard)	33,7 N   192,3 lbf	
Profile design	Without reinforcement	k1% static (standard)	42,1 N   240,4 lbf	
Type of reinforcement	n/a	Weight	21 kg/100m	
Processing Type	n/a	Temperature Range	-20°+60°C	
Recommended Min. pulley $\emptyset$	130 mm	Standard Roll	30 m	
Recommended Pretension	36%	Chemical Resistance	upon request	

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	84° Shore A (±3)	n/a
Color	capri blue	n/a
Diameter Ø	14,3 mm (9/16 inch)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,65   PE: 0,35   HDPE: 0,3	n/a
Features	FDA (Food and Drug Administration)	n/a
n/a	Vegan	n/a
n/a	Metal detectable	n/a
n/a	X-ray detectable	n/a
n/a	n/a	n/a
n/a	n/a	n/a

CONFORMITY
REACH EC 1907/2006 in the current versions
EC 1935/2004 in the current versions
EC 10/2011 in the current versions
FDA (Food and Drug Administration)

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 12/2025