





Quality: PU85A

Article No.: FBZR85A180RA

Color: green



GENERAL PROFILE INFORMATION			
Profile Category	Round belts	Fmax/belt (standard)	92,8 kg
Profile design	with reinforcement	Fmax/Belt (overlap)	204,8 kg
Type of reinforcement	Aramid	Weight	31 kg/100m
Processing Type	n/a	Temperature Range	-20°C+60°C
Recommended Min. pulley Ø	190 mm	Standard Roll	50 m
Recommended Pretension	0.52%	Chemical Resistance	upon request

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	88° Shore A	n/a
Color	green	n/a
Diameter Ø	18 mm (3/4 inch)	n/a
Surface	roughened	n/a
approx. Coefficient of Friction	Steel: 0,45   PE: 0,3   HDPE: 0,25	n/a
Features	with reinforcement	n/a
n/a	n/a	n/a

## CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 10/2025