



Quality: PU85A Article No.: FBRP85A050 Color: green

GENERAL PROFILE INFORMATION				
Round belts	Fmax/belt (standard)		7,1 kg	
Without reinforcement	Fmax/Belt (overlap)		n/a	
n/a	Weight		2,4 kg/100m	
n/a	Temperature Range		-20°+60°C	
50 mm	Standard Roll		100 m	
48%	Chemical Resistance		upon request	
PROFILE		COATING		
Polyurethane		n/a		
88° Shore A		n/a		
	Round belts Without reinforcement n/a n/a 50 mm 48% PROFILE Polyurethane	Round beltsFmax/belt (standard)Without reinforcementFmax/Belt (overlap)n/aWeightn/aTemperature Range50 mmStandard Roll48%Chemical ResistancePROFILEPolyurethane	Round belts Fmax/belt (standard) Without reinforcement Fmax/Belt (overlap) n/a Weight n/a Temperature Range 50 mm Standard Roll 48% Chemical Resistance FROFILE Polyurethane n/a	

Approx. Material Hardness (Shore)	88° Shore A	n/a
Color	green	n/a
Diameter Ø	5 mm (1/5 inch)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,6 PE: 0,35 HDPE: 0,3	n/a
Features	n/a	n/a
n/a	n/a	n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 09/2025