

Round belts

**PU95A red slightly rough, Reinforced Aramid**



Article no.	Diameter $\varnothing$		approx. weight kg/100m	Standard roll		Recommended min. pulley $\varnothing$		DRIVE Fmax/belt		TRANSPORT max. conveying weight			
	mm	inch		m	ft	mm	inch	Standard N	Overlap N	Standard		Overlap	
										kg	lbs	kg	lbs
FBRN095RMA	9,5	3/8	8,5	152	500	175	6,9	177	328	35,4	78,1	65,5	144,4

approx. 95° Shore A ( $\pm 3$ )

Max. Preload

Standard	1,5 %
Overlap	1,5 %

Coeff. of friction  $\mu$  steel approx. 0,4

Coeff. of friction  $\mu$  PE approx. 0,25

Coeff. of friction  $\mu$  HDPE approx. 0,2

FDA/EC compliant

**Characteristics**



**FDA (Food and Drug Administration)**  
 FDA/EC conformity for direct food contact



**Vegan**  
 Use of raw materials from non-animal origin



**with reinforcement**  
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 04/2026