



Quality: TPE55D
Article No.: FBZRH55D063B
Color: beige



| GENERAL PROFILE INFORMATION | | | |
|-----------------------------|----------------------------|------------------------|---------------------|
| Profile Category | Round belts | k1% relaxed (standard) | 74,8 N 426,8 lbf |
| Profile design | with reinforcement | k1% static (standard) | 93,5 N 533,5 lbf |
| Type of reinforcement | Polyester | k1% relaxed (overlap) | 97,0 N 553,3 lbf |
| Processing Type | n/a | k1% static (overlap) | 121,2 N 691,7 lbf |
| Recommended Min. pulley Ø | 85 mm | Standard Roll | 100 m |
| Max. Preload | 2% (Stoß) n/a (Überlapp) | Chemical Resistance | upon request |
| Weight | 3,8 kg/100m | | |
| Temperature Range | -30°...+60°C | | |

| SPECIFICATIONS | PROFILE | COATING |
|-----------------------------------|------------------------------------|---------|
| Type of material | Polyester | n/a |
| Approx. Material Hardness (Shore) | 55D / 100A | n/a |
| Color | beige | n/a |
| Diameter Ø | 6,3 mm (1/4 inch) | n/a |
| Surface | smooth | n/a |
| approx. Coefficient of Friction | Steel: 0,35 PE: 0,2 HDPE: 0,15 | n/a |
| Features | FDA (Food and Drug Administration) | n/a |
| n/a | Vegan | n/a |
| n/a | with reinforcement | n/a |
| n/a | Cold-flexible | n/a |
| n/a | n/a | n/a |
| n/a | n/a | n/a |

| CONFORMITY |
|--|
| REACH EC 1907/2006 in the current versions |
| EC 1935/2004 in the current versions |
| EC 10/2011 in the current versions |
| FDA (Food and Drug Administration) |

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 06/2026