Round belts

TPE55D beige smooth, Reinforced Steel



Article no.	Diameter ø		approx. weight	Standard roll		Recommended min. pulley Øø		DRIVE Fmax/belt		TRANSPORT max. conveying weight			
								Standard	Overlap	Standard		Overlap	
	mm	inch	kg/100m	m	ft	mm	inch	N	N	kg	lbs	kg	lbs
FBRS095BGB	9,5	3/8	8,5	500	1640	380	15		1125			225,0	495,9
FBRS125BGB	12,5	1/2	14,8	500	1640	380	15		1125			225,0	495,9

approx. 55D / 100A	
Max. Preload	
Standard	n/a
Overlap	1 %
Coeff. of friction µ steel approx.	0,35
Coeff. of friction µ PE approx.	0,2
Coeff. of friction µ HDPE approx.	0,15
FDA/EC compliant	

Characteristics

FDA/EC
FDA/EC conformity for direct food contact

Vegan
Use of raw materials from non-animal origin

with reinforcement
for applications that require a higher pull force.

Cold-flexible
Particularly flexible at low temperatures down to -30°C

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 2026-11-23 08:08