

Round belts

TPE63D beige smooth, Reinforced Aramid

Article no.	Diameter Ø		approx. weight	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt		TRANSPORT max. conveying weight			
	mm	inch		m	ft	mm	inch	Standard N	Overlap N	Standard kg	Overlap lbs	Standard kg	Overlap lbs
FBRT095NGC	9,5	3/8	8,5	152	500	190	7,5	284	558	56,7	125,0	111,6	246,0
FBRT125NGC	12,5	1/2	14,8	152	500	270	10,6	491	765	98,2	216,4	153,1	337,4

approx. 63D / 100A

Max. Preload

Standard 1,5 %

Overlap 1,5 %

Coeff. of friction μ steel 0,3 approx.Coeff. of friction μ PE 0,15 approx.Coeff. of friction μ HDPE 0,1 approx.

FDA/EC compliant

Characteristics


FDA (Food and Drug Administration)
 FDA/EC conformity for direct food contact

Vegan
 Use of raw materials from non-animal origin

with reinforcement
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 01/2026