

Round belts

TPE63D beige smooth, Reinforced Polyester



| Article no. | Diameter \varnothing | | approx. weight kg/100m | Standard roll | | Recommended min. pulley \varnothing | | DRIVE Fmax/belt | | TRANSPORT max. conveying weight | | | |
|-------------|------------------------|------|---------------------------|---------------|-----|---------------------------------------|------|-----------------|--------------|---------------------------------|-------|---------|-------|
| | mm | inch | | m | ft | mm | inch | Standard N | Overlap N | Standard | | Overlap | |
| | | | | | | | | | | kg | lbs | kg | lbs |
| FBRT095NGA | 9,5 | 3/8 | 8,5 | 152 | 500 | 190 | 7,5 | 284 | 961 | 56,7 | 125,0 | 192,2 | 423,7 |
| FBRT125NGA | 12,5 | 1/2 | 14,8 | 152 | 500 | 270 | 10,6 | 491 | 1272 | 98,2 | 216,4 | 254,4 | 560,8 |

approx. 63D / 100A

Max. Preload

| | |
|----------|-----|
| Standard | 2 % |
| Overlap | 3 % |

Coeff. of friction μ steel approx. 0,3

Coeff. of friction μ PE approx. 0,15

Coeff. of friction μ HDPE approx. 0,1

FDA/EC compliant

Characteristics



FDA (Food and Drug Administration)
 FDA/EC conformity for direct food contact



Vegan
 Use of raw materials from non-animal origin



with reinforcement
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 04/2026