

Special profiles

PU75A plus orange smooth



Article no.	Dimensions mm	approx. weight kg/100m	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			m	ft	mm	inch	Standard N	Standard kg	Standard lbs
FBPVIPJ20	4.8x4	1,96	200	656	30	1,2	14	2,9	6,3
FBPVIPJ30	7x4	2,93	200	656	30	1,2	22	4,3	9,5
FBPVIPJ40	9.3x4	3,92	200	656	30	1,2	29	5,8	12,7

approx. 80° Shore A (±3)

Recommended Pretension 3...6%

Coeff. of friction μ steel approx. 0,7

Coeff. of friction μ PE approx. 0,4

Coeff. of friction μ HDPE approx. 0,35

Characteristics



Cold-flexible
Particularly flexible at low temperatures down to -30°C



Low elongation
Patented "PLUS" material mix for reduced elongation.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 04/2026