



Quality: PU75A plus
Article No.: FBPVIPJ40
Color: orange



GENERAL PROFILE INFORMATION			
Profile Category	Poly-V belts	k1% relaxed (standard)	4,8 N 27,4 lbf
Profile design	Without reinforcement	k1% static (standard)	6,0 N 34,2 lbf
Type of reinforcement	n/a	Weight	3,92 kg/100m
Processing Type	n/a	Temperature Range	-30°C...+50°C
Recommended Min. pulley Ø	30 mm	Standard Roll	200 m
Recommended Pretension	3...6%	Chemical Resistance	upon request

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	80° Shore A (±3)	n/a
Color	orange	n/a
Dimensions	9.3x4 mm	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,7 PE: 0,4 HDPE: 0,35	n/a
Features	Cold-flexible	n/a
n/a	Low elongation	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 12/2025