

## Special profiles

### PU85A plus ultramarine blue smooth



Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
	mm	kg/100m	m	ft	mm	inch	Standard N	Standard kg	Standard lbs
FBPVKPJ2L	4.8x4	1,96	200	656	40	1,6	31	6,1	13,5
FBPVKPJ3L	7x4	2,93	200	656	40	1,6	46	9,2	20,3
FBPVKPJ4L	9.3x4	3,92	200	656	40	1,6	61	12,3	27,1

approx. 88° Shore A

Recommended Pretension	3...6%
------------------------	--------

Coeff. of friction $\mu$ steel approx.	0,6
--	-----

Coeff. of friction $\mu$ PE approx.	0,35
-------------------------------------	------

Coeff. of friction $\mu$ HDPE approx.	0,3
---------------------------------------	-----

#### Characteristics



**Low elongation**  
Patented "PLUS" material mix for reduced elongation.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 12/2025