



**Quality: PU85A**  
**Article No.: FBSK17X13SG**  
**Color: black**

**GENERAL PROFILE INFORMATION**

Profile Category	Special V-belts	k1% relaxed (standard)	48,0 N   273,8 lbf
Profile design	Without reinforcement	k1% static (standard)	60,0 N   342,3 lbf
Type of reinforcement	n/a	Weight	2,3 kg/100m
Processing Type	n/a	Temperature Range	-20°...+60°C
Recommended Min. pulley Ø	160 mm	Standard Roll	50 m
Recommended Pretension	3...6%	Chemical Resistance	upon request

<b>SPECIFICATIONS</b>	<b>PROFILE</b>	<b>COATING</b>
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	88° Shore A (±3)	n/a
Color	black	n/a
Dimensions	17x13.5 mm	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,6   PE: 0,3   HDPE: 0,25	n/a
Features	n/a	n/a
n/a	n/a	n/a

**CONFORMITY**

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 01/2026