



Quality: PU85A
Article No.: FBSK15X10LG
Color: sapphire blue









GENERAL PROFILE INFORMATION				
Profile Category	Special Profiles	Fmax/belt (standard)	41 kg	
Profile design	Without reinforcement	Fmax/Belt (overlap)	n/a	
Type of reinforcement	n/a	Weight	14 kg/100m	
Processing Type	n/a	Temperature Range	-30°+60°C	
Recommended Min. pulley Ø	100 mm	Standard Roll	30 m	
Recommended Pretension	48%	Chemical Resistance	upon request	

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	88° Shore A	n/a
Color	sapphire blue	n/a
Dimensions	15x10 mm	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,6 PE: 0,35 HDPE: 0,3	n/a
Features	Hydrolysis resistance	n/a
n/a	microbial resistant	n/a
n/a	Cold-flexible	n/a
n/a	FDA (Food and Drug Administration)	n/a
n/a	n/a	n/a
n/a	n/a	n/a

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 10/2025