

T-Profiles

**PU65A ultramarine blue smooth**



Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley Ø		DRIVE	TRANSPORT	
			mm	kg/100m	m	ft	mm	inch	Standard
			N					kg	lbs
FBTG15X5LG	15x5	5,3	50	164	30	1,2			

approx. 72° Shore A (±3)

Recommended Pretension 4...8%

Coeff. of friction  $\mu$  steel approx. 0,8

Coeff. of friction  $\mu$  PE approx. 0,5

Coeff. of friction  $\mu$  HDPE approx. 0,45

FDA/EC compliant

**Characteristics**



**FDA (Food and Drug Administration)**  
FDA/EC conformity for direct food contact



**Vegan**  
Use of raw materials from non-animal origin



**Hydrolysis resistance**  
Hydrolysis resistance (HY). Suitable for humid environments.



**microbial resistant**  
Microbial resistant materials do not provide a breeding ground for microorganisms.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 06/2026