

T-Profiles

PU65A ultramarine blue smooth

Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley ØØ		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			mm	kg/100m	m	ft		Standard N	Standard kg
FBTG95X35LA	9.5x3.5	2,4			70	230	20	0,8	

approx. 72° Shore A (± 3)

Recommended Pretension 4...8%

Coeff. of friction μ steel approx. 0,8Coeff. of friction μ PE approx. 0,5Coeff. of friction μ HDPE approx. 0,45

FDA/EC compliant

Characteristics**Hydrolysis resistance**

Hydrolysis resistance (HY). Suitable for humid environments.

**microbial resistant**

Microbial resistant materials do not provide a breeding ground for microorganisms.

**Cold-flexible**

Particularly flexible at low temperatures down to -30°C

**FDA (Food and Drug Administration)**

FDA/EC conformity for direct food contact

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 01/2026