

# Twin V-belts

## PU80A orange smooth



approx. 84° Shore A (±3)

Recommended Pretension 3...6%

Coeff. of friction  $\mu$  steel approx. 0,65

Coeff. of friction  $\mu$  PE approx. 0,35

Coeff. of friction  $\mu$  HDPE approx. 0,3

FDA/EC compliant

Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley $\varnothing$		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			m	ft	mm	inch	Standard N	Standard kg	Standard lbs
FBSJ24X680GB	24x6,8	14,4	30	100	60	2,4	151	30,2	66,6
FBSP80A21X8	21x8	14	30	100	80	3,1	151	30,2	66,6
FBSJ30X80G	30x8	22,4	30	100	80	3,1	239	47,9	105,5
FBSJ30X80GC	30x8	22,4	30	100	80	3,1	239	47,9	105,5

### Characteristics



**FDA (Food and Drug Administration)**

FDA/EC conformity for direct food contact



**Vegan**

Use of raw materials from non-animal origin

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 05/2026