

Twin V-belts

PU80A orange smooth, Reinforced Polyester



Article no.	Dimensions mm	approx. weight kg/100m	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt		TRANSPORT max. conveying weight			
			m	ft	mm	inch	Standard N	Overlap N	Standard		Overlap	
									kg	lbs	kg	lbs
FBSJ21X80GA	21x8	14,4	30	100	80	3,1	151	341	30,2	66,6	68,1	150,1
FBSJ30X80GD	30x8	22,4	30	100	80	3,1	239	385	47,9	105,5	76,9	169,6

approx. 84° Shore A (±3)

Max. Preload

Standard 2 %

Overlap 3 %

Coeff. of friction μ steel approx. 0,65

Coeff. of friction μ PE approx. 0,35

Coeff. of friction μ HDPE approx. 0,3

FDA/EC compliant

Characteristics



FDA (Food and Drug Administration)

FDA/EC conformity for direct food contact



Vegan

Use of raw materials from non-animal origin



with reinforcement

for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 04/2026