



Quality: PU85A
Article No.: FBSK30X8GGA
Color: mint green



GENERAL PROFILE INFORMATION

Profile Category	Twin V-belts	k1% relaxed (standard)	190,0 N 1084,0 lbf
Profile design	with reinforcement	k1% static (standard)	237,5 N 1354,9 lbf
Type of reinforcement	Polyester	k1% relaxed (overlap)	166,7 N 950,8 lbf
Processing Type	n/a	k1% static (overlap)	208,3 N 1188,5 lbf
Recommended Min. pulley Ø	100 mm	Standard Roll	30 m
Max. Preload	2% (Stoß) n/a (Überlapp)	Chemical Resistance	upon request
Weight	22,4 kg/100m		
Temperature Range	-20°...+60°C		

SPECIFICATIONS

PROFILE

COATING

Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	88° Shore A (±3)	n/a
Color	mint green	n/a
Dimensions	30x8 mm	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,6 PE: 0,35 HDPE: 0,3	n/a
Features	with reinforcement	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 05/2026