


## Twin V-belts

### PU95A beige smooth



Article no.	Dimensions	Cross section	approx. weight	Standard roll		Recommended min. pulley Ø		Fmax/belt (standard)	
	mm	cm <sup>2</sup>	kg/100m	m	ft	mm	inch	kg	lbs
FBSJ24X68BGB	24x6.8	1,26	15	30	100	100	3,9	62,1	136,6
FBSJ30X8BGB	30x8	1,9	22,4	50	164	120	4,72	n/a	n/a

approx. 95° Shore A

Recommended Pretension	3...5%
------------------------	--------

Coeff. of friction $\mu$ steel approx.	0,45
--	------

Coeff. of friction $\mu$ PE approx.	0,25
-------------------------------------	------

Coeff. of friction $\mu$ HDPE approx.	0,2
---------------------------------------	-----

FDA/EC compliant

#### Characteristics



**FDA (Food and Drug Administration)**

FDA/EC conformity for direct food contact



**Vegan**

Use of raw materials from non-animal origin

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 10/2025