Twisted round belts / Hook belts

PU70A sky blue smooth



approx. 76° Shore A	
Recommended pretension	8...10%
Coeff. of friction µ steel approx.	0,75
Coeff. of friction µ PE approx.	0.45
Coeff. of friction µ HDPE approx.	0.40
FDA/EC compliant	

Order No.	Diameter ø		Manufacturing length*	approx. weight	Standard roll	Recommended min. pulley Øø		Fmax/belt (standard)	
	mm	inch	m	kg/100m	piece	mm	inch	kg	lbs
FBXH3X250LG	5	1/5	250	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X270LG	5	1/5	270	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X280LG	5	1/5	280	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X290LG	5	1/5	290	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X310LG	5	1/5	310	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X330LG	5	1/5	330	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X350LG	5	1/5	350	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X370LG	5	1/5	370	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X390LG	5	1/5	390	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X410LG	5	1/5	410	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X430LG	5	1/5	430	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X450LG	5	1/5	450	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X470LG	5	1/5	470	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X490LG	5	1/5	490	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X510LG	5	1/5	510	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X520LG	5	1/5	520	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X530LG	5	1/5	530	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X550LG	5	1/5	550	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X610LG	5	1/5	610	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X660LG	5	1/5	660	n/a	1/50/500	35	1,4	2,5	5,5
FBXH3X710LG	5	1/5	710	n/a	1/50/500	35	1,4	2,5	5,5

*Production lengths without hooks. Further lengths on request.

Characteristics

FDA/EC
FDA/EC conformity for direct food contact

Vegan
Use of raw materials from non-animal origin

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 11/2026