



**Quality:** PU85A  
**Article no.:** FBXK3X710GR  
**Color:** green



**GENERAL PROFILE INFORMATION**

Profile category	Twisted round belts	k1% relaxiert (Stoß)	3,5 N   19,8 lbf
Profile design	Without reinforcement	k1% statisch (Stoß)	4,3 N   24,7 lbf
Type of reinforcement	n/a	Weight	n/a kg/100m
Processing type	n/a	Temperature range	-20°...+60°C
Recommended Min. pulley Ø	50 mm	Standard roll	1/50/500 m
Recommended pretension	6...8%	Chemical resistance	upon request

**SPECIFICATIONS**

**PROFILE**

**COATING**

Type of material	Polyurethane	n/a
Approx. material hardness (Shore)	88° Shore A (±3)	n/a
Color	green	n/a
Diameter Ø	5 mm (1/5 inch)	n/a
Surface	roughened	n/a
Coefficient de friction $\mu$ (approx.)	Steel: 0,45   PE: 0,3   HDPE: 0,25	n/a
Characteristics	Low elongation	n/a
n/a	n/a	n/a

**CONFORMITY**

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 04/2026