


V-Belts

PU75A light grey smooth, Reinforced Polyester



Article no.	Dimensions mm	approx. weight kg/100m	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt		TRANSPORT max. conveying weight			
			m	ft	mm	inch	Standard N	Overlap N	Standard		Overlap	
									kg	lbs	kg	lbs
FBKI13AHGA	13x8 (A)	10	50	164	75	3	111	221	22,3	49,1	44,1	97,2
FBKI17BHGA	17x11 (B)	18	50	164	100	3,9	198	610	39,7	87,4	122,1	269,0
FBKI22CHGA	22x14 (C)	29	50	164	140	5,5	331	909	66,2	145,8	181,7	400,5

approx. 80° Shore A (±3)

Max. Preload

Standard	2 %
Overlap	3 %

Coeff. of friction μ steel approx. 0,7

Coeff. of friction μ PE approx. 0,4

Coeff. of friction μ HDPE approx. 0,35

Characteristics



with reinforcement
 for applications that require
 a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 06/2026