


V-Belts

PU75A light grey smooth, Reinforced Polyester



Article no.	Dimensions	Cross section	approx. weight	Standard roll		Recommended min. pulley Ø		Fmax/belt (standard)		Fmax/belt (overlap)	
	mm	cm ²	kg/100m	m	ft	mm	inch	kg	lbs	kg	lbs
FBKI13AHGA	13x8 (A)	0,82	10	50	164	75	3	20,6	45,3	41,2	90,4
FBKI17BHGA	17x11 (B)	1,46	18	50	164	100	3,9	37,2	81,9	83,8	184,4
FBKI22CHGA	22x14 (C)	2,4	29	50	164	140	5,5	60,8	133,7	127,5	280,5

approx. 80° Shore A

Recommended Pretension	0.5...2%
------------------------	----------

Coeff. of friction μ steel approx.	0,7
--	-----

Coeff. of friction μ PE approx.	0,4
-------------------------------------	-----

Coeff. of friction μ HDPE approx.	0,35
---------------------------------------	------

Characteristics



with reinforcement
for applications that require
a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 09/2025