V-Belts

PU75A orange smooth, Reinforced Glass fibre PU, weldable

Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley ∅ø		DRIVE Fmax/belt		TRANSPORT max. conveying weight			
							Standard	Overlap	Standard		Overlap	
	mm	kg/100m	m	ft	mm	inch	N	N	kg	lbs	kg	lbs
FBZKP75A13GL	13x8 (A)	10	50	164	110	4,4	97		19,3	42,6		
FBZKP75A17GL	17x11 (B)	18	50	164	140	5,5	172		34,4	75,9		
FBZKP75A22GL	22x14 (C)	29	50	164	180	7,1	204		40,9	90,1		

approx. 80° Shore A (±3)	
Max. Preload	
Standard	n/a
Overlap	n/a
Coeff. of friction µ steel approx.	0,7
Coeff. of friction µ PE approx.	0,4
Coeff. of friction µ HDPE approx.	0,35

Characteristics

with reinforcement
for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 11/2026