





Quality: PU85A

Article No.: FBKK17BLGAAA
Color: sapphire blue









GENERAL PROFILE INFORMATION				
Profile Category	V-belts	k1% relaxed (standard)	33,5 N 191,4 lbf	
Profile design	Without reinforcement	k1% static (standard)	41,9 N 239,2 lbf	
Type of reinforcement	n/a	Weight	18 kg/100m	
Processing Type	n/a	Temperature Range	-30°+60°C	
Recommended Min. pulley Ø	120 mm	Standard Roll	50 m	
Recommended Pretension	48%	Chemical Resistance	upon request	

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	88° Shore A (±3)	n/a
Color	sapphire blue	n/a
Dimensions	17x11 mm (B)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,6 PE: 0,35 HDPE: 0,3	n/a
Features	Hydrolysis resistance	n/a
n/a	microbial resistant	n/a
n/a	Cold-flexible	n/a
n/a	FDA (Food and Drug Administration)	n/a
n/a	n/a	n/a
n/a	n/a	n/a

CONFORMITY
REACH EC 1907/2006 in the current versions
EC 1935/2004 in the current versions
EC 10/2011 in the current versions
FDA (Food and Drug Administration)

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 12/2025